

Product Information ORUN-010

GUANGDONG ORUN PETROCHEMICAL CO., LTD TEL: +86 757 81264752 Internet: http://www.terzo-tech.com E-mail: info@terzo-tech.com

Multipure 5W30

Description

A modern, Fully synthetic, universal motor oil based on special selected synthetic base oils, among others ester, with a high viscosity index and a well balanced choice of advanced additives to obtain the following properties:

- a high and very stable viscosity index
- a high resistance against shearing
- a fast cold start
- a very strong resistance against oxidation
- a safe lubrication film at very high temperatures
- a very good detergency and dispersion
- a very strong protection against wear, corrosion and foaming

Application

This universal, ester fortified, fuel saving synthetic motor oil is suitable for use in petrol and diesel engines, with or without turbo-charging. Moreover this lubricant is also very suitable for passenger car diesel engines with pump-injector-unit. This product meets the requirements of several OEM 's and thus has a wide application.

Specifications

Performance level: ACEA C3 API SP, API SN Plus BMW Longlife-04 GM dexos 2 MB 229.31/229.51/229.52 Opel OV0401547 VW 502.00 and 505.00

Typicals

Density at 20 °C, kg/l	0,853
Viscosity -30 °C, mPa.s	5660
Viscosity 40 °C, mm ² /s	66,25
Viscosity 100 °C, mm ² /s	11,18
Viscosity Index	162
Flash Point COC, °C	232
Pour Point, °C	-42
Total Base Number, mgKOH/g	7,13
Sulphate Ash, %	0,72
HTHS viscosity@150, mPa⋅s	3,5