

Product Information ORUN-008

GUANGDONG ORUN PETROCHEMICAL CO., LTD TEL: +86 757 81264752 Internet: http://www.terzo-tech.com E-mail: info@terzo-tech.com

Specialsynth 0W20

Description

A fuel economy SAE 0W20 motor oil, developed according the most recent technology, based on specially selected synthetic base oils and a well balanced choice of advanced additives to obtain the following properties:

- a high fuel economy
- a high and stable viscosity index
- a good resistance against shearing
- a very fast cold start, even at very low temperatures
- a safe lubrication film at very high temperatures
- a very good detergency and dispersion power
- a very strong protection against wear, corrosion and foaming

Application

A fuel economy, specially formulated engine oil suitable for petrol and diesel engines of Volvo cars where the manufacturer prescribes a product that meets the specification VCC RBS0-2AE with viscosity SAE 0W20.

Specifications

Performance level: API SP

ILSAC GF-6

Typicals

Density at 20 °C, kg/l	0,844
Viscosity -35 °C, mPa.s	5032
Viscosity 40 °C, mm ² /s	43,33
Viscosity 100 °C, mm ² /s	8,57
Viscosity Index	165
Flash Point COC, °C	228
Pour Point, °C	-46
Total Base Number, mgKOH/g	8,15
Sulphate Ash, %	0,76
HTHS viscosity@150, mPa·s	2,7