

GUANGDONG ORUN PETROCHEMICAL CO., LTD
 TEL: +86 757 81264752
 Internet: <http://www.terzo-tech.com>
 E-mail: info@terzo-tech.com

SuperSynth 0W30

Description

A modern, fully synthetic, fuel economy motor oil based on special selected synthetic base oils with a high viscosity index and a well balanced choice of advanced additives to obtain the following properties:

- a lower fuel consumption
- a high and very stable viscosity index
- a high resistance against shearing
- a very fast cold start
- a very strong resistance against oxidation
- a safe lubrication film at very high temperatures
- a very good detergency and dispersion
- a very strong protection against wear, corrosion and foaming

Application

A modern fuel economy, special composed synthetic motor oil suitable for use in petrol and diesel engines of passenger cars and delivery vans. This oil is fully backward compatible with BMW Longlife-14 FE+.

Specifications

API SP ACEA C2 ,

Typicals

Density at 20 °C, kg/l	0,840
Viscosity -35 °C, mPa.s	5680
Viscosity 40 °C, mm²/s	58,2
Viscosity 100 °C, mm²/s	10,8
Viscosity Index	171
Flash Point COC, °C	236
Pour Point, °C	-42
Total Base Number, mgKOH/g	8,32
Sulphate Ash, %	0,78
HTHS viscosity@150, mPa.s	3,2