

GUANGDONG ORUN PETROCHEMICAL CO., LTD
 TEL: +86 757 81264752
 Internet: <http://www.terzo-tech.com>
 E-mail: info@terzo-tech.com

SynthGen 5W30

Description

This sophisticated full-synthetic fuel economy universal motor oil is produced with high quality synthetic base oils with a high viscosity index and a well-balanced choice of advanced additives to obtain the following properties:

- a lower fuel consumption
- a high and very stable viscosity index
- a high resistance against shearing
- a fast cold start
- a safe lubrication film at very high temperatures
- a very good detergency and dispersion
- a very strong protection against wear, corrosion and foaming

Application

This universal fuel economy synthetic motor oil is recommended for use in petrol- and diesel engines, with or without turbo-charging, in passenger cars and delivery vans with the specifications as stated below.

Specifications

Performance
 APISN PLUS API SP

Typicals

Density at 20 °C, kg/l	0,853
Viscosity -25 °C, mPa.s	5160
Viscosity 40 °C, mm²/s	64,63
Viscosity 100 °C, mm²/s	11,07
Viscosity Index	166
Flash Point COC, °C	230
Pour Point, °C	-39
Total Base Number, mgKOH/g	7,32
Sulphate Ash, %	0,78
HTHS viscosity@150, mPa.s	3,2